# NEWTON 3
## HL 10 102 00

*HS Code : 85131000*
*Barcode : 3700671407791*




**400** Lumens

**100g** Weight

**80m** Range

**IP65** Rating

**Li-Po** Battery (3,8V / 1100 mAh) (supplied)

**2m** Shock Resistant

**USB Type-C** Charger (supplied)

| | Brightness | Running Time |
|---|---|---|
| Focused 100% | 400 lumens | 2 hours 20 mins* |
| Focused 50% | 200 lumens | 4 hours 30 mins* |
| Focused 5% | 20 lumens | 18 hours* |
| Flood 100% | 400 lumens | 2 hours 20 mins* |

Charging time: 3h30
Charging indicator: Red - charging
Green - full

*with Li-Po battery

### Dimensions

**69 x 46 x 39 mm** / Printed box: 171 x 109 x 50 mm

### Safety

Directive **2014/30/UE**
**2001/95/UE**
**2011/65/UE**
**2012/19/UE**

CE

**LED Risk(c): Group 0 (no risk) - No photobiological hazard. Measures under NF EN 62471 Standard.**

## Assets

- **Hybrid Battery type: 3AAA Alkaline or Li-Po battery**

- Wide light beam (up to 90°).

- IP65: Excellent water and dust resistance.

- Easy to use: Only two buttons.

## Use

**Flood** for working near feet area; **Focused** for work within easy reach.

**Indication of remaining capacity in the battery** <10% the light will blink 3 times.

**Temperatures:** -10°C / +40°C.

**Application:** Industry, Construction, Maintenance, Roadworks, Networks & Work at height (also suitable for leisure, climbing and outdoor activities).